



Uniprise Solutions

9703128/00 | OFE-CLS-J-012

J Closure, 5.0 in OD, two drop ports, one 12-fiber tray

Construction Materials

Material Type Molded plastic

Dimensions

Diameter 127.0 mm | 5.0 in
Length 515.62 mm | 20.30 in

Environmental Specifications

Environmental Space Above ground | Below ground
Operating Temperature -40 °C to +66.5 °C (-40 °F to +151.7 °F)
Qualification Standards Telcordia GR-20-CORE

General Specifications

Splice Trays, quantity 4
Splices, quantity 48
Application For loose tube, central tube, micro-sheath/duct, and blown fiber cable
Color Black
Includes Mounting hardware | Splice tray
Package, quantity 1

Mechanical Specifications

Cable Entry Drop Port Size 25.0 mm | 1.0 in
Cable Entry Drop Port, quantity 2
Cable Entry Express Port Size 25.0 mm | 1.0 in
Cable Entry Express Port, quantity 2

Packed Dimensions

Shipping Weight 3.6 kg | 8.0 lb

Included Products

9703145/00 | OFE-CLS-J-MNT-POL/AIR — Mounting Hardware for J Closure for Pole and Aerial Mounting
9703148/00 | OFE-CLS-J-SPT-12 — Splice tray for J Closure for 12 Single Fusion Splices

Uniprise Solutions

9703150/00 | OFE-CLSJ/K/L-G-ABC

A,B, C Grommets for 0.39–1.0 in cables, three sizes

Construction Materials

Material Type Urethane

Dimensions

Compatible Cable Diameter, maximum 25.4 mm | 1.0 in

Compatible Cable Diameter, minimum 9.9 mm | 0.4 in

General Specifications

Product Type	Grommet
Color	Blue
Includes	Additional plugs Drive piece Grease Knock out plug L bracket Splice nut Tape
Package, quantity	3

Mechanical Specifications

Cables per Grommet 1

Packed Dimensions

Shipping Weight 0.2 kg | 0.4 lb

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system



Uniprise Solutions

9703151/00 | OFE-CLSJ/K/L-G-2H

Single Grommet, two holes, for (0.27–0.47 in cables)

Construction Materials

Material Type Urethane

Dimensions

Compatible Cable Diameter, maximum 11.9 mm | 0.5 in

Compatible Cable Diameter, minimum 6.9 mm | 0.3 in

General Specifications

Product Type	Grommet
Color	Blue
Includes	Additional plugs Drive piece Grease Knock out plug L bracket Splice nut Tape
Package, quantity	1

Mechanical Specifications

Cables per Grommet 2

Packed Dimensions

Shipping Weight 0.2 kg | 0.4 lb

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system



Uniprise Solutions

9703152/00 | OFE-CLSJ/K/L-G-4H

Single Grommet, four holes, for 0.11–0.27 in cables

Construction Materials

Material Type Urethane

Dimensions

Compatible Cable Diameter, maximum 6.9 mm | 0.3 in

Compatible Cable Diameter, minimum 2.8 mm | 0.1 in

General Specifications

Product Type	Grommet
Color	Blue
Includes	Additional plugs Drive piece Grease Knock out plug L bracket Splice nut Tape
Package, quantity	1

Mechanical Specifications

Cables per Grommet 4

Packed Dimensions

Shipping Weight 0.3 kg | 0.6 lb

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

